

KOLLEZI

○ WALL



WWW.KOLLEZI.COM

O WALL

Technical Information

*Valid valve and rough-in position before installation

In-wall conceal tank.....Metal frame
 Bearing capacity.....400 kg | 880 lb
 Residential installation.....2" x4" & 6" stud wall
 Flush type.....Dual flush
 Water consumption.....0.8/1.6 GPF | 3/6 LPF
 Flush action.....Gravity flush down
 Outlet pipe.....Ø 4" | 100 mm
 Inlet pipe.....Ø 2" | 50mm
 Rough-in.....In-wall floor
 Mounting holes.....7-9" | 180-230 mm
 Dual flush button K4117.....Included
 Warranty.....5 years
 All product dimensions are nominal

Information Technique

*Valider la position de la valve d'alimentation et la plomberie brute avant l'installation

Système de réservoir mural.....Cadre de métal
 Capacité portante.....400 kg | 880 lb
 Installation résidentielle.....2" x4" & 6" Colomage
 Type de chasseDouble chasse
 Consommation d'eau.....0.8/1.6 GPF | 3/6 LPF
 Fonction de chasse.....Gravité directe
 Tuyau de décharge.....Ø 4" | 100 mm
 Tuyau d'entréeØ 2" | 50 mm
 Installation/plomberie brute.....Plancher mural
 Trous d'installation.....7-9" | 180-230 mm
 Bouton de chasse duo K4117.....Inclus
 Garantie.....5 ans
 Toutes les dimensions sont nominales

